



DERBIGUM®
MAKING BUILDINGS SMART

DECLARATION OF PERFORMANCE N° P106A-V1-EN

1 - Unique identification Code of the product type:

P106A-DERBIGUM SP AR

2 - Identification of the construction product, in accordance with article 11(4)

DERBIGUM SP AR / Lot number: see on product or on labelling or product packaging

3 – Intended use(s) of the construction product:

Reinforced bituminous sheet for roof waterproofing (Roof Garden)

4 - Name, registered trade name or registered trade mark and contact address of the manufacturer in accordance with article 11(5):

DERBIGUM-IMPERBEL sa/nv, Chaussée de Wavre, 67 B-1360 Perwez (Belgium)

5 – Name and contact address of authorised representative in accordance with article 12(2):

Not applicable

6 - System(s) of assessment and verification of constancy of performance of the product as set out in Annex V

AVCP 2+

7 – In case of the declaration of performance concerning a construction product covered by a harmonised standard :

BCCA- Belgian Construction Certification Association (Notified Body n°0749) :

- performed the inspection of the factory production control under system 2+

- and issued certificate of conformity of the factory production control

n° BC2-310-0305-0123-01 (EN 13707 : 2004 + A2 : 2009)

8 – In case of the declaration of performance concerning a construction product for which a European technical assessment has been issued:

Not applicable



DERBIGUM®

MAKING BUILDINGS SMART

9 – Declared performances following harmonized technical specification
EN 13707 : 2004 + A2 : 2009

| Essential characteristics | Performances | Units |
|--|-------------------------------------|--------------------|
| External fire performance (Note 1) | FRoof (t1, t2, t3, t4) | - |
| Reaction to fire | E | - |
| Watertightness | Pass | - |
| Tensile strength : Maximum tensile force LxT* Elongation at maximum tensile force LxT* | 700 x 650 (± 20%) 45 x 45 (± 15) | N/50 mm % |
| Root Resistance | Pass | - |
| Resistance to static loading method A | 20 | kg |
| Resistance to impact method A and B | 1250 | mm |
| Resistance to tearing LxT* | 200 x 200 (±25%) | N |
| Joint strength : Peel resistance Shear resistance | 65 (± 20%) 560 (± 20%) | N/50 mm N/50 mm |
| Durability : UV Heat and water Pliability after heat oven exposure | Pass -10 (± 5) | - °C |
| Pliability | -15 | °C |
| Dangerous Substances | (Note 2) | - |

* L means longitudinal direction, T means transverse direction

Note 1: No performance can be given The external fire performance of a roof is dominated by the built up system

Note 2: In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use

10 – The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by:

Mr Steve Geubels,
Group Operations Director

Perwez , 21/06/2013